



## NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X =  $\pm 0.4$   
X.XX =  $\pm 0.25$
3. TERM. NUMBERS FOR REFERENCE ONLY.
4. CONTACT RATING: 0.2A @ 30VDC
5. TRAVEL: 3.0 mm
- ▲ 6. OPERATING FORCE:  $200 \pm 100\text{gf}$
7. LIFE EXPECTANCY: 10,000 CYCLES
8. OPERATING TEMP:  $-20^{\circ}\text{C}$  to  $70^{\circ}\text{C}$
9. ▲ DENOTES CRITICAL PARAMETER
10. 2011/65/EU (ROHS) COMPLIANT



TITLE EG1201A (SOLDER LUG, NON-SHORTING)

C	23226	Drawing updated and redrawn	2/20/18	MW
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY  
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE	DATE	DR	DWG	REV
2:1	2/20/2018	MW	P040011	C

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[EG1201A](#)